

# WHY SHOULD I CHOOSE HARD FLOOR CASTERS?

New office chairs are typically equipped with hard caster wheels intended to be used on carpeted floor. But what if the chair ends up on a hard surface such as hardwood, VCT, ceramic tile, concrete, etc? Rolling the hard caster wheels on hard flooring can scratch or permanently damage your expensive hardwood, linoleum or tile floors. An additional benefit is a reduction in noise level in the workplace.

Solution? Replace the existing hard caster wheels with polyurethane caster wheels. The slightly softer polyurethane material will help prevent the wheels from scratching the hard floor while allowing the wheels to roll smoothly and quietly.

Besides cosmetic, safety is another reason why polyurethane caster wheels should be used on hard flooring. Polyurethane provides better traction on hard floor thus reducing the chance of accidental slipping.



## HARD SURFACE CASTER



Premium hard floor caster. Hooded. 2" dia.  
**CP**

**CPS** Shroudless



Premium hard floor caster. Hooded. 2.5" dia.  
**CK**



Casters lock while seated. 2" dia.  
**CPL<sup>ON</sup>**



Weight release activates brake to prevent chair from moving when not in use. 2" dia.  
**CPL<sup>OFF</sup>**

**NOTE:**  
ALL CASTERS ARE SOLD  
IN SETS OF 5 (FIVE).

**CARPET CASTER**



Standard hooded carpet caster. 2" dia.

**CH**

**CS** Shroudless



Premium carpet caster. Hooded. 2.5" dia.

**CH-60**

**SPECIALTY CASTERS**



**Size:** 2.5" diameter dual wheel  
**Material:** Grey, non-marking Thermoplastic Elastomer  
**Capacity:** 100 lbs per caster  
**Application:** Medical  
**TP**



**Size:** 2" diameter  
**Material:** Grey, non-marking Neoprene, Chrome plated finish  
**Capacity:** 125 lbs per caster  
**Application:** Medical  
**Note:** Can be disassembled for cleaning  
**NP**



**Size:** 3" diameter  
**Material:** Grey, non-marking Polyurethane "Dyna-Tred", Zinc finish  
**Capacity:** 90 lbs per caster  
**Application:** Extreme, factory, warehouse  
**Resistance:** Resists chemicals, acids, caustic, and oils  
**Temperature:** Range of -40°C to 82°C  
**BXNL-E**



**Size:** 3" diameter  
**Material:** Grey, non-marking Monopreme, Zinc finish  
**Capacity:** 120 lbs per caster  
**Application:** Medical  
**BXNL-M**



**Size:** 3" diameter  
**Material:** Black, non-marking Polyolefin, Zinc finish  
**Capacity:** 120 lbs per caster  
**Application:** Medical, factory, warehouse  
**BX** With lock  
**BXNL** Without lock



**Size:** 2.5" diameter  
**Material:** Black, non-marking Neoprene, Chrome plated finish  
**Capacity:** 165 lbs per caster  
**Application:** Medical  
**Note:** Can be disassembled for cleaning  
**Option:** Total lock brake  
**NP25** Without lock  
**NP25L** With lock



**NSF:** National Sanitation Foundation listed  
**Material:** Grey, non-marking rubber, Zinc finish  
**Capacity:** 75 lbs per caster  
**Application:** Food service, Sanitary environments  
**Note:** Can be disassembled for cleaning  
**NSF2** 2" diameter  
**NSF3** 3" diameter

**NOTE:**  
**ALL CASTERS ARE SOLD IN SETS OF 5 (FIVE).**